

Direct-View LED Traffic Controller TCL718GR-140

PRODUCT NUMBER

5895

CABINET DIMENSIONS

7" H x 18" W x 2.5" D

ILLUMINATION SOURCE

Super bright, wide viewing angle LEDs
Available in green, red, blue, amber, and white LEDs
Messages "blankout" when turned off, eliminating confusion
Long life, solid state lighting

ELECTRICAL

Integrated solid state power supply
Standard Voltage: 120 VAC, Optional Voltages: 9-36 V, 240 VAC, 277 VAC
Maximum amps per lighted message (at 120 V) shown in the table below
UL/CUL approved for wet locations

CONSTRUCTION

Faces: Single Faced Sign
Extrusion (TCL): Slim line, corrosion resistant all weather frame 2.5" thick.
Face Material: Impact Resistant, smoked tinted Polycarbonate 1/8" thick.



FINISH

Standard Cabinet Color: Duranodic Bronze
Custom colors available upon request



Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



MESSAGE	COLOR	HEIGHT	AMPS
OPEN	Green Wide Angle Oval	3.5"	0.03
IN USE	Red Wide Angle Oval	3.5"	0.02

iSigns
7625 Birkmire Drive
Fairview, PA 16415



Proudly Made in the USA