## PRODUCT ID: 25930

Outdoor Blank-out LED Backlit Sign

#### MODEL

PHX734G-165/120-277VAC



#### DIMENSIONS

7" H x 34" W x 2.25" D (est. 7.151 lbs)

## **CLASS**

Class: PHX Series

Control Method: Switch (not included) or external relay.

## CONSTRUCTION

Cabinet: 1-piece, corrosion resistant, extruded all-weather frame, 2.25" deep. Face Material: 1/8" thick, dark grey diffused acrylic

Faces: Single Faced Sign

Finish: Duranodic Bronze Mounting Channel: None

## **ELECTRICAL**

Flashing: Not Included Input Voltage: 120-277 VAC
UL/cUL Listed: Listed for wet locations

## **MESSAGE**

Color: Black opaque Font: Swiss 721 Bold BT

Illumination: Backlit with high intensity LEDs. Message blanks out when off

Sign Messages: See message table below

#### **MESSAGE** LED/COLOR | HEIGHT | AMPS

24 HR ATM Green Wide Angle LED | 3.75" | 0.347-0.150

NOTE: Above messages are independently controlled.

#### iSIGNS Inc.

7625 Birkmire Drive Fairview, PA 16415 Phone: 866-437-3040 Website: www.isignsled.com




Proudly Made in the USA

# **Product View**

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.





Frame Detail

