

## PRODUCT ID: 26032

### Outdoor Blank-out LED Backlit Sign

#### MODEL

PHX734GR-220/120-277VAC



#### DIMENSIONS

7" H x 34" W x 2.25" D (est. 7.182 lbs)

#### CLASS

Class: PHX Series

Control Method: Switch (not included) or external relay.

#### CONSTRUCTION

Cabinet: 1-piece, corrosion resistant, extruded all-weather frame, 2.25" deep.

Face Material: 1/8" thick, dark grey diffused acrylic

Faces: Single Faced Sign

Finish: Duranodic Bronze

Graphic: Printed graphic applied to surface

Mounting Channel: None

#### ELECTRICAL

Flashing: Not Included

Input Voltage: 120-277 VAC

UL/cUL Listed: Listed for wet locations

#### MESSAGE

Color: Black opaque

Font: Swiss 721 Bold BT

Illumination: Backlit with high intensity LEDs. Message blanks out when off

Sign Messages: See message table below

| MESSAGE | LED/COLOR            | HEIGHT | AMPS        |
|---------|----------------------|--------|-------------|
| OPEN    | Green Wide Angle LED | 3.75"  | 0.173-0.075 |
| FULL    | Red Wide Angle LED   | 3.75"  | 0.116-0.050 |

NOTE: Above messages are independently controlled.

#### iSIGNS Inc.

7625 Birkmire Drive

Fairview, PA 16415

Phone: 866-437-3040

Website: [www.isignsled.com](http://www.isignsled.com)




innovative sign technologies inc.

Proudly Made in the USA

## Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



### Sample Display Options



### Frame Detail

