

Direct-View LED Traffic Controller DOT1426RG-132

PRODUCT NUMBER

34132

CABINET DIMENSIONS

14" H x 26" W x 5" D



ILLUMINATION SOURCE

Application specific, Super bright, Narrow and/or Wide viewing angle LEDs
Message LED angles and colors noted in the table below
Messages "blankout" when turned off, eliminating confusion
Long life, solid state lighting

ELECTRICAL

(3) Redundant Photocells for auto photodimming
Power Supplies: (2) Redundant power supplies per message
Input Voltage: 85-264VAC Universal Input, Max amps shown in the table below
UL/CUL approved for wet locations

CONSTRUCTION

Faces: Single Faced Sign
Cabinet: (DOT): NEMA 4X Rated, 6063-T6 aluminum continuous extruded profile with 1/8" wall thickness with chemically bonded and welded seams. Optional Visor
Door: Continuous hinge with a 1" silicone gasket and stainless steel tool free lockable door latches
Face Material: Impact resistant, 1/4" thick polycarbonate

FINISH

Standard Cabinet Color: Semi-gloss Black T241-BK59 polyester powder coat

Note: Other LED colors, voltages and cabinet paint colors available upon request.

MESSAGE	COLOR	HEIGHT	AMPS
DO NOT ENTER	Red Wide Angle Oval	2.5"	0.03
ENTER	Green Wide Angle Oval	3.5"	0.04

iSigns
7625 Birkmire Drive
Fairview, PA 16415



Proudly Made in the USA

Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.

