

**PRODUCT ID: 34355**  
**DOT LED Blank-Out Sign**

**MODEL**  
 DOT2424RG-175/100-240VAC



**DIMENSIONS**  
 24" H x 24" W x 5" D (est. 39.017 lbs)

**CLASS**  
 Class: DOT Series  
 Control Method: Switch (not included) or external relay.

**CONSTRUCTION**  
 Cabinet: Extruded aluminum cabinet with welded seams, NEMA 4X rated/IP66.  
 Hinged door with 1" silicone gasket, tool-less stainless-steel latches. 5.0" Deep.  
 Face Material: Replaceable 1/4" thick smoke-tinted polycarbonate (5109)  
 Faces: Single Faced Sign  
 Finish: Powdercoat Black  
 Integral Hood: Optional hood available  
 Mounting Channel: None

**ELECTRICAL**  
 Input Voltage: 100-240 VAC  
 Photodimming: (3) Redundant fail-safe photocells for auto photodimming  
 Power Supplies: Redundant  
 UL/cUL Listed: Listed for wet locations

**MESSAGE**  
 Illumination: Super bright direct view LEDs. Message blanks out when off.  
 Sign Messages: See message table below

| MESSAGE    | LED/COLOR              | HEIGHT | AMPS        |
|------------|------------------------|--------|-------------|
| X          | Red Narrow Angle LED   | 16.75" | 0.187-0.078 |
| Down Arrow | Green Narrow Angle LED | 17.5"  | 0.222-0.093 |

NOTE: Above messages are independently controlled.


iSIGNS Inc.  
 7625 Birkmire Drive  
 Fairview, PA 16415  
 Phone: 866-437-3040  
 Website: [www.isignsled.com](http://www.isignsled.com)



Proudly Made in the USA

**Product View**

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



**Sample Display Options**

