

PRODUCT ID: 39606

Outdoor Blank-out LED Backlit Sign

MODEL

PHX1434RR-K166



DIMENSIONS

14" H x 34" W x 2.25" D (est. 11.495 lbs)

CLASS

Class: PHX Series

Control Method: Switch (not included) or external relay.

CONSTRUCTION

Cabinet: 1-piece, corrosion resistant, extruded all-weather frame, 2.25" deep.

Face Material: 1/8" thick, dark grey diffused acrylic

Faces: Single Faced Sign

Finish: Duranodic Bronze

Mounting Channel: None

ELECTRICAL

Flashing: Not Included

Input Voltage: 120-277 VAC

UL/cUL Listed: Listed for wet locations

MESSAGE

Color: Black opaque

Font: Swiss 721 Bold BT

Illumination: Backlit with high intensity LEDs. Message blanks out when off

Sign Messages: See message table below

Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



MESSAGE	LED/COLOR	HEIGHT	AMPS
STILL GRADING	Red Wide Angle LED	3.0"	0.231-0.100
REJECT CONTACT OPERATOR	Red Wide Angle LED	1.625"	0.231-0.100

NOTE: Above messages are independently controlled.

iSIGNS Inc.
7625 Birkmire Drive
Fairview, PA 16415
Phone: 866-437-3040
Website: www.isignsled.com



Proudly Made in the USA

Sample Display Options

