

PRODUCT ID: 43572

Outdoor Blank-out LED Backlit Sign

MODEL

PHX1442GGR-A143



DIMENSIONS

14" H x 42" W x 2.25" D (est. 10.323 lbs)

CLASS

Class: PHX Series

Control Method: Switch (not included) or external relay.

CONSTRUCTION

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.25" deep.

Face Material: 1/8" thick, dark grey diffused acrylic

Faces: Single Faced Sign

Finish: Duranodic Bronze

ELECTRICAL

Flashing: Not Included

Input Voltage: 120-277 VAC

UL/cUL Listed: Listed for wet locations

MESSAGE

Font: Swiss 721 Bold BT

Illumination: Backlit with high intensity LEDs. Message blanks out when off

Sign Messages: See message table below

Vinyl Color: Black opaque vinyl

NOTE: Other LED colors, voltages, cabinet sizes, styles, and colors available.


Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



MESSAGE	LED/COLOR	HEIGHT	AMPS
COMMERCIAL LANE	Green Wide Angle LED	3.0"	0.930-0.403
OPEN	Green Wide Angle LED	3.5"	0.310-0.134
CLOSED	Red Wide Angle LED	3.5"	0.200-0.087

NOTE: Above messages are independently controlled.



iSIGNS Inc.

7625 Birkmire Drive

Fairview, PA 16415

Phone: 866-437-3040

Website: www.isignsled.com



Proudly Made in the USA