

PRODUCT ID: 40797
DOT LED Blank-Out Sign

MODEL
 DOT2167GR-100/100-240VAC



DIMENSIONS
 21" H x 67" W x 5" D (est. 99.918 lbs)

CLASS
 Class: DOT Series
 Control Method: Switch (not included) or external relay.

CONSTRUCTION
 Cabinet: Extruded aluminum cabinet with welded seams, NEMA 4X rated/IP66. Hinged door with 1" silicone gasket, tool-less stainless-steel latches. 5.0" Deep.
 Face Material: Replaceable 1/4" thick smoke-tinted polycarbonate (5109)
 Faces: Single Faced Sign
 Finish: Powdercoat Black
 Integral Hood: Single piece 1/8" brake formed aluminum hood. Depth (13.0" Deep)
 Mounting Channel: None

ELECTRICAL
 Input Voltage: 100-240 VAC
 Photodimming: (3) Redundant fail-safe photocells for auto photodimming
 Power Supplies: Redundant
 UL/cUL Listed: Listed for wet locations

MESSAGE
 Illumination: Super bright direct view LEDs. Message blanks out when off.
 Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
OPEN	Green Wide Angle LED	12.0"	0.213-0.089
CLOSED	Red Wide Angle LED	12.0"	0.162-0.067

NOTE: Above messages are independently controlled.


iSIGNS Inc.
 7625 Birkmire Drive
 Fairview, PA 16415
 Phone: 866-437-3040
 Website: www.isignsled.com



Proudly Made in the USA

Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Sample Display Options

