

PRODUCT ID: 50092

Outdoor Blank-out LED Backlit Sign

MODEL

PHX1434WGR-K601/120-277VAC



DIMENSIONS

14" H x 34" W x 2.25" D (est. 11.123 lbs)

CLASS

Class: PHX Series

Control Method: Switch (not included) or external relay.

CONSTRUCTION

Cabinet: 1-piece, corrosion resistant, extruded all-weather frame, 2.25" deep.

Face Material: 1/8" thick, dark grey diffused acrylic

Faces: Single Faced Sign

Finish: Duranodic Bronze

Graphic: Printed graphic applied to surface

Mounting Channel: None

ELECTRICAL

Flashing: Not Included

Input Voltage: 120-277 VAC

UL/cUL Listed: Listed for wet locations

MESSAGE

Color: Black opaque

Font: Swiss 721 Bold BT

Illumination: Backlit with high intensity LEDs. Message blanks out when off

Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
LANE 6	White Wide Angle LED	3.5"	0.347-0.150
OPEN	Green Wide Angle LED	3.5"	0.173-0.075
CLOSED	Red Wide Angle LED	3.5"	0.116-0.050

NOTE: Above messages are independently controlled.

iSIGNS Inc.

7625 Birkmire Drive

Fairview, PA 16415

Phone: 866-437-3040


Website: www.isignsled.com



Proudly Made in the USA

Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Sample Display Options

